

EARPLUGS

MAXIMUM LITE

Minimum Pressure. Maximum Comfort.

Overview



Feedback

Honeywell MAXIMUM LITE earplugs are designed to ensure minimum pressure and maximum comfort in a disposable earplug.

- Contoured T-shape for easy handling and wear.
- Low pressure polyurethane foam expands gently for comfortable long-term wear.
- Ideal size for workers with smaller ear canals.
- Smooth, soil-resistant closed-cell foam skin prevents dirt build-up.
- Corded and uncorded versions available with various dispensing options.

Earplug Fitting & Maintenance Recommendations

Inspect: Prior to fitting, examine your earplugs.

Discard: Discard disposable earplugs after each use, or if earplugs are compromised.

Hygiene: To maintain hygiene standards, disposable earplugs should be discarded at the end of every shift.

Fitting

- With clean hands, roll the entire earplug into narrowest possible crease-free cylinder.
- Reach over your head with a free hand, pull your ear up and back, and insert the earplug well inside your ear canal.
- Hold for 30 – 40 seconds, until the earplug fully expands in your ear canal. If properly fitted, the end of the earplugs should not be visible to someone looking at you from the front.

Improper fit of this device will reduce its effectiveness in attenuating noise. Refer to instructions on package for proper fit.

Recommended Industries/Use

- Agriculture
- Chemical
- Construction
- Fire Protection
- Forestry
- Government
- Law Enforcement
- Manufacturing
- Medical
- Military
- Mining
- Municipal Services
- Oil and Gas
- Pharmaceutical
- Steel and Metals
- Transportation

- Utilities
- Welding

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EC Directive/PPE
- Category II - EC Category/PPE
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)
- 9001:2008 - ISO

Specifications

OTHERS

Single Number Rating <ul style="list-style-type: none"> • 34 decibel 	Detectable <ul style="list-style-type: none"> • No 	High Visibility <ul style="list-style-type: none"> • Yes
Corded <ul style="list-style-type: none"> • Corded/Uncorded 	Certifications; Standards; Specifications Met <ul style="list-style-type: none"> • EN 352-2-2002: ANSI S3.19-1974: AS/NZS 1270-2002 	SLC80 Rating <ul style="list-style-type: none"> • 25 (Class 4)
Earplug Shape <ul style="list-style-type: none"> • Contoured T-Shape 	Earplug Size <ul style="list-style-type: none"> • One Size Fits All 	Canada Class <ul style="list-style-type: none"> • A (L)
Material <ul style="list-style-type: none"> • Polyurethane Foam 	Cord Color <ul style="list-style-type: none"> • Yellow 	Features & Benefits <ul style="list-style-type: none"> • Low pressure polyurethane foam expands gently for comfortable long-term wear. Ideal size for workers with smaller ear canals. Contoured T-shape for easy handling and wear. Smooth soil-resistant closed-cell foam skin prevents dirt build-up.
Care and Maintenance <ul style="list-style-type: none"> • Inspect: Prior to fitting, examine your earplugs. 	Earplug Type <ul style="list-style-type: none"> • Roll-down Foam 	Standards & Certifications <ul style="list-style-type: none"> • EN 352-2-1993: ANSI S3.19-1974: AS/NZS 1270-2002
Reusability <ul style="list-style-type: none"> • Disposable 	Product Family <ul style="list-style-type: none"> • Howard Leight 	Noise Reduction Rating <ul style="list-style-type: none"> • 30 • 30 decibel

Feedback

Product Number

SKU	DESCRIPTION
HL400-LPF-INTRO	HL400 Dispenser with 1 prefilled canister of 400 pairs of Maximum Lite earplugs. UOM = CS
HL400-LPF-REFILL	HL400 Prefilled Canister, Maximum Lite Earplugs Uncorded, Prefilled Canister Refill for HL400, UOM = CS, 400 Pairs per Canister, 2 Canisters per Case, 800 Pairs per Case
LPF-1	MAXIMUM LITE, Contoured T-Shape Polyurethane Foam Uncorded Earplugs, Polybag, UOM = CS, 2000 Pairs per Case, 10 Boxes per Case, 200 Pairs per Box
LPF-1-D	MAXIMUM LITE, Bulk Refill, Leight Source 500 T-Shape Polyurethane Foam Uncorded Earplugs
LPF-1-O-BULK	MAXIMUM LITE-ORANGE,NO CORD,BULK, UOM=CASE, 8000 Pairs per Case

LPF-1-PB	Uncorded, Paperbag, UOM = CS, 1000 Pairs per Case, 10 Boxes per Case, 100 Pairs per Box
LPF-30	MAXIMUM LITE, Contoured T-Shape Polyurethane Foam Earplugs, Corded, Polybag, UOM = CS, 1000 Pairs per Case, 10 Boxes per Case, 100 Pairs per Box;
LPF-30-P	Honeywell Howard Leight Maximum Lite Contoured T-Shape Polyurethane Foam Corded Earplugs
LPF-30-PB	Honeywell Howard Leight Maximum Lite Contoured T-Shape Polyurethane Foam Corded Earplugs
LPF-5	MAXIMUM LITE, Contoured T-Shape Polyurethane Foam Uncorded Earplugs, 5 Pr Polybag, UOM = CS, 2500 Pairs per Case, 50 Bags per Box, 10 Boxes per Case

Honeywell

Safety and Productivity
Solutions
855 S Mint St
Charlotte, NC 28202
800-582-4263

MAXIMUM LITE

© 2024 Honeywell International Inc.
All rights reserved.



This document was generated on 2024-03-06 09:47:02 (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.